



FAG

4309-B-TVH-C3

Deep groove ball bearing

Deep groove ball bearing 43.-B-TVH, double row, plastic cage

Informacje techniczne



Twoja aktualna wersja produktu

Design variant	B	Bearing without filling slot
Tolerance class	PN	Normal (ISO 492:2023)
Cage	TVH	Solid cage made of glass-fiber reinforced polyamid PA66
Lubricant	Lubricating grease	
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN

Main Dimensions & Performance Data

d	45 mm	Bore diameter
D	100 mm	Outside diameter
B	36 mm	Width
C _r	75.000 N	Basic dynamic load rating, radial
C _{0r}	60.000 N	Basic static load rating, radial
C _{ur}	3.700 N	Fatigue load limit, radial
n _G	6.300 1/min	Limiting speed
n _{gr}	5.300 1/min	Reference speed
≈m	1,22 kg	Masa

Mounting dimensions

d _{a min}	54 mm	Minimum diameter shaft shoulder
D _{a max}	91 mm	Maximum diameter of housing shoulder
r _{a max}	1,5 mm	Maximum fillet radius



Dimensions

r _{min}	1,5 mm	Minimum chamfer dimension
D ₁	86,84 mm	Shoulder diameter outer ring
d ₁	66,7 mm	Shoulder diameter inner ring

Temperature range

T _{min}	-20 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Calculation factors

f ₀	13,9	Calculation factor
----------------	------	--------------------

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie smarem
	Bez uszczelnienia