





FAG

51140-MP

Axial deep groove ball bearing

Axial deep groove ball bearing 511..-MP,
single direction, solid brass cage

Informacje techniczne



Twoja aktualna wersja produktu

Cage	MP	Solid brass cage, rolling element guided
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S1	Rings dimensional stabilized up to 200°

Main Dimensions & Performance Data

d	200 mm	Inner diameter shaft washer
D	250 mm	Outer diameter housing washer
T	37 mm	Height
C _a	162.000 N	Basic dynamic load rating, axial
C _{0a}	670.000 N	Basic static load rating, axial
C _{ua}	20.400 N	Fatigue load limit, axial
n _G	1.980 1/min	Limiting speed
n _{gr}	1.760 1/min	Reference speed

Mounting dimensions

d _{a min}	230 mm	Minimum diameter shaft shoulder
D _{a max}	220 mm	Maximum diameter of housing shoulder
r _{a max}	1 mm	Maximum filled radius



Dimensions

r _{min}	1,1 mm	Minimum chamfer dimension
D ₁	203 mm	Inner diameter housing washer
d ₁	247 mm	Outer diameter shaft washer

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	200 °C	Operating temperature max.

Calculation factors

A	2,5	Minimum load factor
---	-----	---------------------

Właściwości

-  Obciążenie osiowe jednokierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia