




FAG

53232-MP

Axial deep groove ball bearing

Axial deep groove ball bearing 532...-MP, single direction, with spherical housing washer, solid brass cage

Informacje techniczne



Twoja aktualna wersja produktu


Cage	MP	Solid brass cage, rolling element guided
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°

Main Dimensions & Performance Data

d	160 mm	Inner diameter shaft washer
D	225 mm	Outer diameter housing washer
T	54,7 mm	Height
C _a	240.000 N	Basic dynamic load rating, axial
C _{0a}	770.000 N	Basic static load rating, axial
C _{ua}	25.500 N	Fatigue load limit, axial
n _G	1.900 1/min	Limiting speed
n _{gr}	2.350 1/min	Reference speed
≈m	6,315 kg	Masa

Mounting dimensions

d _{a min}	199 mm	Minimum diameter shaft shoulder
D _{a max}	190 mm	Maximum diameter of housing shoulder
r _{a max}	1,5 mm	Maximum filled radius



Dimensions

r _{min}	1,5 mm	Minimum chamfer dimension
D ₁	163 mm	Inner diameter housing washer
d ₁	222 mm	Outer diameter shaft washer
R	160 mm	Radius spherical housing washer
A	74 mm	Distance of the center point
T ₁	61 mm	Height with seat washer
D ₂	190 mm	Bore diameter seat washer
D ₃	235 mm	Outside diameter seat washer
C	21 mm	Height seat washer

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	150 °C	Operating temperature max.

Calculation factors

A	3,2	Minimum load factor
---	-----	---------------------

Additional information

U232	Seat washer
------	-------------

Właściwości

	Obciążenie osiowe jednokierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia
	Nieosiowość statyczna