



**FAG****6017-Z-C3**

Deep groove ball bearing

Deep groove ball bearing 60...-Z, single row, shield, steel sheet metal cage

Informacje techniczne



Twoja aktualna wersja produktu

Type of Seal	Z	Non-contact shield on one Side
Cage	JN	Steel sheet metal
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Lubricant	Without	Bearing not greased
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	85 mm	Bore diameter
D	130 mm	Outside diameter
B	22 mm	Width
C _r	53.000 N	Basic dynamic load rating, radial
C _{0r}	43.000 N	Basic static load rating, radial
C _{ur}	2.500 N	Fatigue load limit, radial
n _G	7.100 1/min	Limiting speed
n _{gr}	5.800 1/min	Reference speed
≈m	0,87 kg	Masa



Mounting dimensions

$d_{a\ min}$	91 mm	Minimum diameter shaft shoulder
$D_{a\ max}$	124 mm	Maximum diameter of housing shoulder
$r_{a\ max}$	1 mm	Maximum fillet radius

Dimensions

$r_{\min}$	1,1 mm	Minimum chamfer dimension
D_1	116,04 mm	Shoulder diameter outer ring
D_2	119,24 mm	Caliber diameter outer ring
d_1	99,2 mm	Shoulder diameter inner ring

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	150 °C	Operating temperature max.

Calculation factors

f_0	15,7	Calculation factor
-------	------	--------------------

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Uszczelnienie jednostronne