


FAG

6024-M-C3

Deep groove ball bearing

Deep groove ball bearing 60.-M, single row, solid brass cage

Informacje techniczne



Twoja aktualna wersja produktu

Sealing	Without	Not sealed
Cage	M	Solid brass cage, rolling element guided
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Lubricant	Without	Bearing not greased
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	120 mm	Bore diameter
D	180 mm	Outside diameter
B	28 mm	Width
C _r	88.000 N	Basic dynamic load rating, radial
C _{0r}	77.000 N	Basic static load rating, radial
C _{ur}	3.650 N	Fatigue load limit, radial
n _G	6.500 1/min	Limiting speed
n _{gr}	4.450 1/min	Reference speed
≈m	2,64 kg	Masa



Mounting dimensions

d a min	128,8 mm	Minimum diameter shaft shoulder
D a max	171,2 mm	Maximum diameter of housing shoulder
r a max	2 mm	Maximum fillet radius

Dimensions

r min	2 mm	Minimum chamfer dimension
D 1	161,38 mm	Shoulder diameter outer ring
d 1	139,82 mm	Shoulder diameter inner ring

Temperature range

T min	-30 °C	Operating temperature min.
T max	150 °C	Operating temperature max.

Calculation factors

f 0	15,8	Calculation factor
-----	------	--------------------

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia