



FAG

6040-M-C4

Deep groove ball bearing

Deep groove ball bearing 60...-M, single row, solid brass cage

Informacje techniczne



Twoja aktualna wersja produktu

Sealing	Without	Not sealed
Cage	M	Solid brass cage, rolling element guided
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S1	Rings dimensional stabilized up to 200°
Lubricant	Without	Bearing not greased
Radial internal clearance	C4 (Group 4)	Internal clearance larger than C3
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	200 mm	Bore diameter
D	310 mm	Outside diameter
B	51 mm	Width
C _r	231.000 N	Basic dynamic load rating, radial
C _{0r}	243.000 N	Basic static load rating, radial
C _{ur}	9.900 N	Fatigue load limit, radial
n _G	3.650 1/min	Limiting speed
n _{gr}	3.000 1/min	Reference speed
≈m	14,3 kg	Masa



Mounting dimensions

$d_{a\ min}$	210,2 mm	Minimum diameter shaft shoulder
$D_{a\ max}$	299,8 mm	Maximum diameter of housing shoulder
$r_{a\ max}$	2,1 mm	Maximum fillet radius

Dimensions

$r_{\ min}$	2,1 mm	Minimum chamfer dimension
D_1	276,25 mm	Shoulder diameter outer ring
d_1	234,84 mm	Shoulder diameter inner ring

Temperature range

$T_{\ min}$	-30 °C	Operating temperature min.
$T_{\ max}$	200 °C	Operating temperature max.

Calculation factors

f_0	15,6	Calculation factor
-------	------	--------------------

Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Obciążenie osiowe dwukierunkowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia