


FAG

618/670-M

Deep groove ball bearing

Deep groove ball bearing 618..-M, single row, solid brass cage

Informacje techniczne



Twoja aktualna wersja produktu

Type of Seal	Without	Not sealed
Cage	M	Solid brass cage, rolling element guided
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S1	Rings dimensional stabilized up to 200°
Lubricant	Without	Bearing not greased
Radial internal clearance	CN (Group N)	Normal internal clearance
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	670 mm	Bore diameter
D	820 mm	Outside diameter
B	69 mm	Width
C _r	445.000 N	Basic dynamic load rating, radial
C _{0r}	910.000 N	Basic static load rating, radial
C _{ur}	19.300 N	Fatigue load limit, radial
n _G	1.250 1/min	Limiting speed
n _{gr}	760 1/min	Reference speed
≈m	76 kg	Masa



Mounting dimensions

$d_{a\min}$	684,6 mm	Minimum diameter shaft shoulder
$D_{a\max}$	805,4 mm	Maximum diameter of housing shoulder
$r_{a\max}$	3 mm	Maximum fillet radius

Dimensions

$r_{\min}$	4 mm	Minimum chamfer dimension
D_1	774,3 mm	Shoulder diameter outer ring
d_1	719,8 mm	Shoulder diameter inner ring

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	200 °C	Operating temperature max.

Calculation factors

f_0	15,9	Calculation factor
-------	------	--------------------

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia
	Łożysko gabarytowe