



**FAG****61900-2RSR>N**

Deep groove ball bearing

Deep groove ball bearing 619...-2RSR, single row, seals, steel sheet metal cage

Informacje techniczne



Twoja aktualna wersja produktu

Version code	>N	Not marked on bearing
Type of Seal	2RSR	Contact seal on both sides
Cage	JN	Steel sheet metal
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	Lubricating grease	
Radial internal clearance	CN (Group N)	Normal internal clearance
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	10 mm	Bore diameter
D	22 mm	Outside diameter
B	6 mm	Width
C _r	2.850 N	Basic dynamic load rating, radial
C _{0r}	1.270 N	Basic static load rating, radial
C _{ur}	79 N	Fatigue load limit, radial
n _G	19.200 1/min	Limiting speed
≈m	0,01 kg	Masa



Mounting dimensions

$d_{a\ min}$	12 mm	Minimum diameter shaft shoulder
$D_{a\ max}$	20 mm	Maximum diameter of housing shoulder
$r_{a\ max}$	0,3 mm	Maximum fillet radius

Dimensions

$r_{\ min}$	0,3 mm	Minimum chamfer dimension
D_1	18,1 mm	Shoulder diameter outer ring
D_2	19,5 mm	Caliber diameter outer ring
d_1	13,9 mm	Shoulder diameter inner ring
d_2	13,45 mm	Caliber diameter inner ring

Temperature range

$T_{\ min}$	-30 °C	Operating temperature min.
$T_{\ max}$	100 °C	Operating temperature max.

Calculation factors

f_0	14	Calculation factor
-------	----	--------------------

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie dożywotnie, bezobsługowe
	Smarowanie smarem
	Uszczelnienie dwustronne