


FAG

61952-M-C3

Deep groove ball bearing

Deep groove ball bearing 619...-M, single row, solid brass cage

Informacje techniczne



Twoja aktualna wersja produktu

Sealing	Without	Not sealed
Cage	M	Solid brass cage, rolling element guided
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S1	Rings dimensional stabilized up to 200°
Lubricant	Without	Bearing not greased
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	260 mm	Bore diameter
D	360 mm	Outside diameter
B	46 mm	Width
C _r	222.000 N	Basic dynamic load rating, radial
C _{0r}	280.000 N	Basic static load rating, radial
C _{ur}	8.800 N	Fatigue load limit, radial
n _G	3.050 1/min	Limiting speed
n _{gr}	2.180 1/min	Reference speed
≈m	14,2 kg	Masa



Mounting dimensions

$d_{a\ min}$	270,2 mm	Minimum diameter shaft shoulder
$D_{a\ max}$	349,8 mm	Maximum diameter of housing shoulder
$r_{a\ max}$	2,1 mm	Maximum fillet radius

Dimensions

$r_{\ min}$	2,1 mm	Minimum chamfer dimension
$D_{\ 1}$	330 mm	Shoulder diameter outer ring
$d_{\ 1}$	291,1 mm	Shoulder diameter inner ring

Temperature range

$T_{\ min}$	-30 °C	Operating temperature min.
$T_{\ max}$	200 °C	Operating temperature max.

Calculation factors

$f_{\ 0}$	16,3	Calculation factor
-----------	------	--------------------

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia
	Łożysko gabarytowe