




FAG

6201-C-2ELS-C3>V

Deep groove ball bearing

Deep groove ball bearing 62...-C-2ELS, single row, Generation C, steel sheet metal cage

Informacje techniczne



Twoja aktualna wersja produktu

Version code	>V	Not marked on bearing
Changed internal design	C	GenerationC
Type of Seal	2ELS	Contact seal on both sides
Cage	JN	Steel sheet metal
Tolerance class	P6	Class 6 (ISO 492:2023)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	GA14	Ball bearing grease, low noise
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	12 mm	Bore diameter
D	32 mm	Outside diameter
B	10 mm	Width
C _r	8.000 N	Basic dynamic load rating, radial
C _{0r}	3.100 N	Basic static load rating, radial
C _{ur}	213 N	Fatigue load limit, radial
n _G	22.500 1/min	Limiting speed
≈m	0,036 kg	Masa



Mounting dimensions

d a min	16,2 mm	Minimum diameter shaft shoulder
D a max	27,8 mm	Maximum diameter of housing shoulder
r a max	0,6 mm	Maximum fillet radius

Dimensions

r min	0,6 mm	Minimum chamfer dimension
D 1	26 mm	Shoulder diameter outer ring
D 2	27,92 mm	Caliber diameter outer ring
d 1	18,31 mm	Shoulder diameter inner ring
d 2	17,34 mm	Caliber diameter inner ring

Temperature range

T min	-20 °C	Operating temperature min.
T max	100 °C	Operating temperature max.

Calculation factors

f 0	12,3	Calculation factor
-----	------	--------------------

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie dożywotnie, bezobsługowe
	Smarowanie smarem
	Uszczelnienie dwustronne