



FAG


6207-N

Deep groove ball bearing

Deep groove ball bearing 62...-N, single row,
ring groove, steel sheet metal cage



Informacje techniczne



Twoja aktualna wersja produktu

Sealing	Without	Not sealed
Design, bearing outer ring	N	Ring groove for snap ring
Cage	JN	Steel sheet metal
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	Without	Bearing not greased
Radial internal clearance	CN (Group N)	Normal internal clearance
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	35 mm	Bore diameter
D	72 mm	Outside diameter
B	17 mm	Width
C _r	27.500 N	Basic dynamic load rating, radial
C _{0r}	15.300 N	Basic static load rating, radial
C _{ur}	950 N	Fatigue load limit, radial
n _G	13.800 1/min	Limiting speed
n _{gr}	10.400 1/min	Reference speed
≈m	291,49 g	Masa



Mounting dimensions

d a min	42 mm	Minimum diameter shaft shoulder
D a max	65 mm	Maximum diameter of housing shoulder
r a max	1 mm	Maximum fillet radius

Dimensions

r min	1,1 mm	Minimum chamfer dimension
D 1	60,66 mm	Shoulder diameter outer ring
D 2	63,34 mm	Caliber diameter outer ring
d 1	47,2 mm	Shoulder diameter inner ring

Temperature range

T min	-30 °C	Operating temperature min.
T max	120 °C	Operating temperature max.

Calculation factors

f 0	13,8	Calculation factor
-----	------	--------------------

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia