




FAG

6208-C-2Z-C3>V

Deep groove ball bearing

Deep groove ball bearing 62...-C-2Z, single row, Generation C, shields, steel sheet metal cage

Informacje techniczne



Twoja aktualna wersja produktu

Version code	>V	Not marked on bearing
Changed internal design	C	GenerationC
Sealing	2Z	Non-contact shield on both sides
Cage	JN	Steel sheet metal
Tolerance class	P6	Class 6 (ISO 492:2023)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	GA13	Ball bearing and insert bearing grease
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	40 mm	Bore diameter
D	80 mm	Outside diameter
B	18 mm	Width
C _r	33.500 N	Basic dynamic load rating, radial
C _{0r}	17.800 N	Basic static load rating, radial
C _{ur}	1.230 N	Fatigue load limit, radial
n _G	11.600 1/min	Limiting speed
n _{gr}	10.500 1/min	Reference speed
≈m	0,365 kg	Masa



Mounting dimensions

$d_{a\ min}$	47 mm	Minimum diameter shaft shoulder
$D_{a\ max}$	73 mm	Maximum diameter of housing shoulder
$r_{a\ max}$	1 mm	Maximum fillet radius

Dimensions

$r_{\min}$	1,1 mm	Minimum chamfer dimension
D_1	67,6 mm	Shoulder diameter outer ring
D_2	70,56 mm	Caliber diameter outer ring
d_1	51,88 mm	Shoulder diameter inner ring
d_2	49,3 mm	Caliber diameter inner ring

Temperature range

$T_{\min}$	-20 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

Calculation factors

f_0	14	Calculation factor
-------	----	--------------------

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie dożywotnie, bezobsługowe
	Smarowanie smarem
	Uszczelnienie dwustronne