



FAG

6208-N

Deep groove ball bearing

Deep groove ball bearing 62...-N, single row,
ring groove, steel sheet metal cage



Informacje techniczne



Twoja aktualna wersja produktu

Sealing	Without	Not sealed
Design, bearing outer ring	N	Ring groove for snap ring
Cage	JN	Steel sheet metal
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	Without	Bearing not greased
Radial internal clearance	CN (Group N)	Normal internal clearance
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	40 mm	Bore diameter
D	80 mm	Outside diameter
B	18 mm	Width
C _r	31.000 N	Basic dynamic load rating, radial
C _{0r}	17.800 N	Basic static load rating, radial
C _{ur}	1.080 N	Fatigue load limit, radial
n _G	12.300 1/min	Limiting speed
n _{gr}	9.300 1/min	Reference speed
m	0,341 kg	Masa



Mounting dimensions

$d_{a\ min}$	47 mm	Minimum diameter shaft shoulder
$D_{a\ max}$	73 mm	Maximum diameter of housing shoulder
$r_{a\ max}$	1 mm	Maximum fillet radius

Dimensions

$r_{\min}$	1,1 mm	Minimum chamfer dimension
D_1	67,6 mm	Shoulder diameter outer ring
D_2	70,36 mm	Caliber diameter outer ring
d_1	52,95 mm	Shoulder diameter inner ring

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

Calculation factors

f_0	14	Calculation factor
-------	----	--------------------

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia