



FAG

6252-M-C4

Deep groove ball bearing

Deep groove ball bearing 62...-M, single row, solid brass cage

Informacje techniczne



Twoja aktualna wersja produktu

Sealing	Without	Not sealed
Cage	M	Solid brass cage, rolling element guided
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S1	Rings dimensional stabilized up to 200°
Lubricant	Without	Bearing not greased
Radial internal clearance	C4 (Group 4)	Internal clearance larger than C3
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	260 mm	Bore diameter
D	480 mm	Outside diameter
B	80 mm	Width
C _r	410.000 N	Basic dynamic load rating, radial
C _{0r}	560.000 N	Basic static load rating, radial
C _{ur}	19.700 N	Fatigue load limit, radial
n _G	2.370 1/min	Limiting speed
n _{gr}	1.820 1/min	Reference speed
≈m	67,8 kg	Masa



Mounting dimensions

$d_{a \min}$	280 mm	Minimum diameter shaft shoulder
$D_{a \max}$	460 mm	Maximum diameter of housing shoulder
$r_{a \max}$	4 mm	Maximum fillet radius

Dimensions

$r_{\min}$	5 mm	Minimum chamfer dimension
D_1	402,55 mm	Shoulder diameter outer ring
d_1	337,1 mm	Shoulder diameter inner ring

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	200 °C	Operating temperature max.

Calculation factors

f_0	15,1	Calculation factor
-------	------	--------------------

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia
	Łożysko gabarytowe