


**FAG****6301-H-2RSR>N**

Deep groove ball bearing

Deep groove ball bearing 63...-H-2RSR, single row, H-Series, seals, steel sheet metal cage

Informacje techniczne



Twoja aktualna wersja produktu

Version code	>N	Not marked on bearing
Changed internal design	H	Design variant H (H-Series)
Type of Seal	2RSR	Contact seal on both sides
Cage	JN	Steel sheet metal
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	Lubricating grease	
Radial internal clearance	CN (Group N)	Normal internal clearance
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	12 mm	Bore diameter
D	37 mm	Outside diameter
B	12 mm	Width
C _r	7.690 N	Basic dynamic load rating, radial
C _{0r}	3.500 N	Basic static load rating, radial
C _{ur}	202 N	Fatigue load limit, radial
n _G	13.400 1/min	Limiting speed
≈m	0,064 kg	Masa



Mounting dimensions

$d_{a\min}$	17,6 mm	Minimum diameter shaft shoulder
$D_{a\max}$	31,4 mm	Maximum diameter of housing shoulder
$r_{a\max}$	1 mm	Maximum fillet radius

Dimensions

$r_{\min}$	1 mm	Minimum chamfer dimension
D_1	29,7 mm	Shoulder diameter outer ring
D_2	31,6 mm	Caliber diameter outer ring
d_1	19,4 mm	Shoulder diameter inner ring
d_2	18,2 mm	Caliber diameter inner ring

Temperature range

$T_{\min}$	-20 °C	Operating temperature min.
$T_{\max}$	100 °C	Operating temperature max.

Calculation factors

f_0	12,4	Calculation factor
-------	------	--------------------

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie dożywotnie, bezobsługowe
	Smarowanie smarem
	Uszczelnienie dwustronne