



FAG

6305-C-HRS>V

Deep groove ball bearing

Deep groove ball bearing 63...-C-HRS, single row, Generation C, seal, steel sheet metal cage

Informacje techniczne



Twoja aktualna wersja produktu

Version code	>V	Not marked on bearing
Changed internal design	C	GenerationC
Sealing	HRS	Contact seal on one side
Cage	JN	Steel sheet metal
Tolerance class	P6	Class 6 (ISO 492:2023)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	Without	Bearing not greased
Radial internal clearance	CN (Group N)	Normal internal clearance
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	25 mm	Bore diameter
D	62 mm	Outside diameter
B	17 mm	Width
C _r	26.500 N	Basic dynamic load rating, radial
C _{0r}	11.500 N	Basic static load rating, radial
C _{ur}	790 N	Fatigue load limit, radial
n _G	11.300 1/min	Limiting speed
≈m	0,222 kg	Masa



Mounting dimensions

d a min	32 mm	Minimum diameter shaft shoulder
D a max	55 mm	Maximum diameter of housing shoulder
r a max	1 mm	Maximum fillet radius

Dimensions

r min	1,1 mm	Minimum chamfer dimension
D 1	51,55 mm	Shoulder diameter outer ring
D 2	53,8 mm	Caliber diameter outer ring
d 1	35,45 mm	Shoulder diameter inner ring
d 2	34,12 mm	Caliber diameter inner ring

Temperature range

T min	-30 °C	Operating temperature min.
T max	100 °C	Operating temperature max.

Calculation factors

f 0	12,4	Calculation factor
-----	------	--------------------

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Uszczelnienie jednostronne