



FAG

6308-C-2HRS-L055-C3>V

Deep groove ball bearing

Deep groove ball bearing 63...-C-2HRS, single row, Generation C, seals, steel sheet metal cage

Informacje techniczne



Twoja aktualna wersja produktu

Version code	>V	Not marked on bearing
Changed internal design	C	GenerationC
Type of Seal	2HRS	Contact seal on both sides
Cage	JN	Steel sheet metal
Tolerance class	P6	Class 6 (ISO 492:2023)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	L055	Grease (L055/customer specific)
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	40 mm	Bore diameter
D	90 mm	Outside diameter
B	23 mm	Width
C _r	50.000 N	Basic dynamic load rating, radial
C _{0r}	25.000 N	Basic static load rating, radial
C _{ur}	1.730 N	Fatigue load limit, radial
n _G	7.400 1/min	Limiting speed
≈m	0,626 kg	Masa



Mounting dimensions

d a min	49 mm	Minimum diameter shaft shoulder
D a max	81 mm	Maximum diameter of housing shoulder
r a max	1,5 mm	Maximum fillet radius

Dimensions

r min	1,5 mm	Minimum chamfer dimension
D 1	75,54 mm	Shoulder diameter outer ring
D 2	78,61 mm	Caliber diameter outer ring
d 1	55,08 mm	Shoulder diameter inner ring
d 2	52,28 mm	Caliber diameter inner ring

Temperature range

T min	-30 °C	Operating temperature min.
T max	100 °C	Operating temperature max.

Calculation factors

f 0	13	Calculation factor
-----	----	--------------------

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie dożywotnie, bezobsługowe
	Smarowanie smarem
	Uszczelnienie dwustronne