



FAG

6316-2Z-L138

Deep groove ball bearing

Deep groove ball bearing 63...2Z, single row, shields, steel sheet metal cage

Informacje techniczne



Twoja aktualna wersja produktu

|                                  |              |                                         |
|----------------------------------|--------------|-----------------------------------------|
| Type of Seal                     | 2Z           | Non-contact shield on both sides        |
| Cage                             | JN           | Steel sheet metal                       |
| Tolerance class                  | PN           | Normal (ISO 492:2023)                   |
| Dimensional / heat stabilization | S0           | Rings dimensional stabilized up to 150° |
| Lubricant                        | L138         | Grease (L138/customer specific)         |
| Radial internal clearance        | CN (Group N) | Normal internal clearance               |
| Bore type                        | Z            | Cylindrical                             |

Main Dimensions & Performance Data

|                 |             |                                   |
|-----------------|-------------|-----------------------------------|
| d               | 80 mm       | Bore diameter                     |
| D               | 170 mm      | Outside diameter                  |
| B               | 39 mm       | Width                             |
| C <sub>r</sub>  | 131.000 N   | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 87.000 N    | Basic static load rating, radial  |
| C <sub>ur</sub> | 5.400 N     | Fatigue load limit, radial        |
| n <sub>G</sub>  | 4.550 1/min | Limiting speed                    |
| n <sub>gr</sub> | 5.500 1/min | Reference speed                   |
| ≈m              | 3,82 kg     | Masa                              |



### Mounting dimensions

|             |        |                                      |
|-------------|--------|--------------------------------------|
| $d_{a\min}$ | 92 mm  | Minimum diameter shaft shoulder      |
| $D_{a\max}$ | 158 mm | Maximum diameter of housing shoulder |
| $r_{a\max}$ | 2,1 mm | Maximum fillet radius                |

### Dimensions

|            |           |                              |
|------------|-----------|------------------------------|
| $r_{\min}$ | 2,1 mm    | Minimum chamfer dimension    |
| $D_1$      | 141,92 mm | Shoulder diameter outer ring |
| $D_2$      | 145,48 mm | Caliber diameter outer ring  |
| $d_1$      | 108,2 mm  | Shoulder diameter inner ring |

### Temperature range

|            |        |                            |
|------------|--------|----------------------------|
| $T_{\min}$ | -30 °C | Operating temperature min. |
| $T_{\max}$ | 120 °C | Operating temperature max. |

### Calculation factors

|       |      |                    |
|-------|------|--------------------|
| $f_0$ | 13,3 | Calculation factor |
|-------|------|--------------------|

### Właściwości

|                                                                                     |                                     |
|-------------------------------------------------------------------------------------|-------------------------------------|
|  | Obciążenie promieniowe              |
|  | Obciążenie osiowe jednokierunkowe   |
|  | Obciążenie osiowe dwukierunkowe     |
|  | Smarowanie dożywotnie, bezobsługowe |
|  | Smarowanie smarem                   |
|  | Uszczelnienie dwustronne            |