



FAG

6317-2Z-L069-C3

Deep groove ball bearing

Deep groove ball bearing 63...2Z, single row, shields, steel sheet metal cage

Informacje techniczne



Twoja aktualna wersja produktu

Sealing	2Z	Non-contact shield on both sides
Cage	JN	Steel sheet metal
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Lubricant	L069	Low noise high-temperature grease, interchangeable with grease L207
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	85 mm	Bore diameter
D	180 mm	Outside diameter
B	41 mm	Width
C _r	141.000 N	Basic dynamic load rating, radial
C _{0r}	97.000 N	Basic static load rating, radial
C _{ur}	6.000 N	Fatigue load limit, radial
n _G	4.300 1/min	Limiting speed
n _{gr}	5.300 1/min	Reference speed
m	4,39 kg	Masa



Mounting dimensions

$d_{a\min}$	99 mm	Minimum diameter shaft shoulder
$D_{a\max}$	166 mm	Maximum diameter of housing shoulder
$r_{a\max}$	2,5 mm	Maximum fillet radius

Dimensions

$r_{\min}$	3 mm	Minimum chamfer dimension
D_1	151,58 mm	Shoulder diameter outer ring
D_2	154,9 mm	Caliber diameter outer ring
d_1	114 mm	Shoulder diameter inner ring

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	150 °C	Operating temperature max.

Calculation factors

f_0	13,3	Calculation factor
-------	------	--------------------

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie dożywotnie, bezobsługowe
	Smarowanie smarem
	Uszczelnienie dwustronne