



FAG

6326-C3

Deep groove ball bearing

Deep groove ball bearing 63, single row, steel
sheet metal cage

Informacje techniczne



Twoja aktualna wersja produktu

Sealing	Without	Not sealed
Cage	JN	Steel sheet metal
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S1	Rings dimensional stabilized up to 200°
Lubricant	Without	Bearing not greased
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	130 mm	Bore diameter
D	280 mm	Outside diameter
B	58 mm	Width
C _r	244.000 N	Basic dynamic load rating, radial
C _{0r}	214.000 N	Basic static load rating, radial
C _{ur}	10.100 N	Fatigue load limit, radial
n _G	3.200 1/min	Limiting speed
n _{gr}	3.500 1/min	Reference speed
≈m	15,255 kg	Masa



Mounting dimensions

$d_{a\ min}$	147 mm	Minimum diameter shaft shoulder
$D_{a\ max}$	263 mm	Maximum diameter of housing shoulder
$r_{a\ max}$	3 mm	Maximum fillet radius

Dimensions

$r_{\ min}$	4 mm	Minimum chamfer dimension
$D_{\ 1}$	231,25 mm	Shoulder diameter outer ring
$d_{\ 1}$	178,88 mm	Shoulder diameter inner ring

Temperature range

$T_{\ min}$	-30 °C	Operating temperature min.
$T_{\ max}$	200 °C	Operating temperature max.

Calculation factors

$f_{\ 0}$	13,5	Calculation factor
-----------	------	--------------------

Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia