


FAG

6326-M-J20AA-C4

Deep groove ball bearing

Deep groove ball bearing 63...-M-J20AA,
single row, solid brass cage, ceramic coated

Informacje techniczne



Twoja aktualna wersja produktu

Type of Seal	Without	Not sealed
Cage	M	Solid brass cage, rolling element guided
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S1	Rings dimensional stabilized up to 200°
Lubricant	Without	Bearing not greased
Radial internal clearance	C4 (Group 4)	Internal clearance larger than C3
Bore type	Z	Cylindrical
Coating	J20AA	Current insulation, outer ring ceramic coated

Main Dimensions & Performance Data

d	130 mm	Bore diameter
D	280 mm	Outside diameter
B	58 mm	Width
C _r	244.000 N	Basic dynamic load rating, radial
C _{0r}	214.000 N	Basic static load rating, radial
C _{ur}	10.100 N	Fatigue load limit, radial
n _G	4.150 1/min	Limiting speed
n _{gr}	3.500 1/min	Reference speed
≈m	17,49 kg	Masa



Mounting dimensions

$d_{a\ min}$	147 mm	Minimum diameter shaft shoulder
$D_{a\ max}$	263 mm	Maximum diameter of housing shoulder
$r_{a\ max}$	3 mm	Maximum fillet radius

Dimensions

$r_{\min}$	4 mm	Minimum chamfer dimension
D_1	231,9 mm	Shoulder diameter outer ring
d_1	178,88 mm	Shoulder diameter inner ring

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	200 °C	Operating temperature max.

Calculation factors

f_0	13,5	Calculation factor
-------	------	--------------------

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia
	Izolowane