





FAG

7210-B-XL-TVP-P5-UL 

Angular contact ball bearing

Angular contact ball bearing 72...-B-XL-TVP,
single row, X-life, plastic cage

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design variant	B	B
Type of Seal	Without	Not sealed
Cage	TVP	Solid cage made of glass-fiber reinforced polyamid PA66
Tolerance class	P5	Class 5 (ISO 492:2023)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Bearing with matched conditions for fitting in pairs	UL	Bearing set with light preload
Lubricant	Without	Bearing not greased

Main Dimensions & Performance Data

d	50 mm	Bore diameter
D	90 mm	Outside diameter
B	20 mm	Width
C _r	41.500 N	Basic dynamic load rating, radial
C _{0r}	28.500 N	Basic static load rating, radial
C _{ur}	1.970 N	Fatigue load limit, radial
n _G	10.300 1/min	Limiting speed
n _{gr}	7.600 1/min	Reference speed
≈m	0,46 kg	Masa



Mounting dimensions

d _{a min}	57 mm	Minimum diameter of shaft shoulder
D _{a max}	83 mm	Maximum diameter of housing shoulder
D _{b max}	85,8 mm	Maximum diameter of housing shoulder
r _{a max}	1 mm	Maximum fillet radius of shaft
r _{a1 max}	0,6 mm	Maximum fillet radius of housing

Dimensions

r _{min}	1,1 mm	Minimum chamfer dimension
r _{1 min}	0,6 mm	Minimum chamfer dimension
D ₁	74,78 mm	Shoulder diameter on outer ring wide side face
d ₁	66,26 mm	Shoulder diameter on inner ring wide side face
a	39,4 mm	Distance between the apexes of the pressure cones
α	40 °	Contact angle

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Additional information

V _{max}	-6 μm	Preload per set max.
Tol (+)	6 μm	Tolerance for axial clearance or preload per set
F _{V max}	288 N	Preload force



Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia