



FAG




X-life

7219-B-XL-MP-P5-UL

Angular contact ball bearing

Angular contact ball bearing 72..-B-XL-MP,
single row, X-life, solid brass cage

Informacje techniczne



Twoja aktualna wersja produktu

Design variant	B	B
Sealing	Without	Not sealed
Cage	MP	Solid brass cage, ball guided
Tolerance class	P5	Class 5 (ISO 492:2023)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Bearing with matched conditions for fitting in pairs	UL	Bearing set with light preload
Lubricant	Without	Bearing not greased

Main Dimensions & Performance Data

d	95 mm	Bore diameter
D	170 mm	Outside diameter
B	32 mm	Width
C _r	123.000 N	Basic dynamic load rating, radial
C _{0r}	106.000 N	Basic static load rating, radial
C _{ur}	6.400 N	Fatigue load limit, radial
n _G	6.700 1/min	Limiting speed
n _{gr}	4.450 1/min	Reference speed
m	2,98 kg	Masa



Mounting dimensions

d _{a min}	107 mm	Minimum diameter of shaft shoulder
D _{a max}	158 mm	Maximum diameter of housing shoulder
D _{b max}	163 mm	Maximum diameter of housing shoulder
r _{a max}	2,1 mm	Maximum fillet radius of shaft
r _{a1 max}	1 mm	Maximum fillet radius of housing

Dimensions

r _{min}	2,1 mm	Minimum chamfer dimension
r _{1 min}	1,1 mm	Minimum chamfer dimension
D ₁	141,5 mm	Shoulder diameter on outer ring wide side face
d ₁	125,3 mm	Shoulder diameter on inner ring wide side face
a	71,6 mm	Distance between the apexes of the pressure cones
α	40 °	Contact angle

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	150 °C	Operating temperature max.

Additional information

V _{max}	-10 μm	Preload per set max.
Tol (+)	10 μm	Tolerance for axial clearance or preload per set
F _{V max}	892 N	Preload force



Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia