



FAG

7228-B-XL-MP [🔗](#)

Angular contact ball bearing

Angular contact ball bearing 72..-B-XL-MP,
single row, X-life, solid brass cage



X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design variant	B	B
Type of Seal	Without	Not sealed
Cage	MP	Solid brass cage, ball guided
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S1	Rings dimensional stabilized up to 200°
Lubricant	Without	Bearing not greased

Main Dimensions & Performance Data

d	140 mm	Bore diameter
D	250 mm	Outside diameter
B	42 mm	Width
C _r	214.000 N	Basic dynamic load rating, radial
C _{0r}	231.000 N	Basic static load rating, radial
C _{ur}	11.500 N	Fatigue load limit, radial
n _G	4.450 1/min	Limiting speed
n _{gr}	3.100 1/min	Reference speed

≈m	8,55 kg	Masa
----	---------	------



Mounting dimensions

$d_{a \min}$	154 mm	Minimum diameter of shaft shoulder
$D_{a \max}$	236 mm	Maximum diameter of housing shoulder
$D_{b \max}$	243 mm	Maximum diameter of housing shoulder
$r_{a \max}$	2,5 mm	Maximum fillet radius of shaft
$r_{a1 \max}$	1 mm	Maximum fillet radius of housing

Dimensions

$r_{\min}$	3 mm	Minimum chamfer dimension
$r_{1 \min}$	1,1 mm	Minimum chamfer dimension
D_1	207,5 mm	Shoulder diameter on outer ring wide side face
d_1	183,5 mm	Shoulder diameter on inner ring wide side face
a	102,8 mm	Distance between the apexes of the pressure cones
α	40 °	Contact angle

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	200 °C	Operating temperature max.

Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia