



FAG



X-life

7324-B-XL-MP

Angular contact ball bearing

Angular contact ball bearing 73..-B-XL-MP,
single row, X-life, solid brass cage

Informacje techniczne



Twoja aktualna wersja produktu

Design variant	B	B
Type of Seal	Without	Not sealed
Cage	MP	Solid brass cage, ball guided
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S1	Rings dimensional stabilized up to 200°
Lubricant	Without	Bearing not greased

Main Dimensions & Performance Data

d	120 mm	Bore diameter
D	260 mm	Outside diameter
B	55 mm	Width
C _r	275.000 N	Basic dynamic load rating, radial
C _{0r}	285.000 N	Basic static load rating, radial
C _{ur}	14.300 N	Fatigue load limit, radial
n _G	4.350 1/min	Limiting speed
n _{gr}	2.850 1/min	Reference speed
≈m	14,05 kg	Masa



Mounting dimensions

$d_{a\ min}$	134 mm	Minimum diameter of shaft shoulder
$D_{a\ max}$	246 mm	Maximum diameter of housing shoulder
$D_{b\ max}$	253 mm	Maximum diameter of housing shoulder
$r_{a\ max}$	2,5 mm	Maximum fillet radius of shaft
$r_{a1\ max}$	1 mm	Maximum fillet radius of housing

Dimensions

$r_{\ min}$	3 mm	Minimum chamfer dimension
$r_{1\ min}$	1,1 mm	Minimum chamfer dimension
D_1	207,1 mm	Shoulder diameter on outer ring wide side face
d_1	176,38 mm	Shoulder diameter on inner ring wide side face
a	107,2 mm	Distance between the apexes of the pressure cones
α	40 °	Contact angle

Temperature range

$T_{\ min}$	-30 °C	Operating temperature min.
$T_{\ max}$	200 °C	Operating temperature max.

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia