



FAG


7352-B-MP-UA

Angular contact ball bearing

Angular contact ball bearing 73..-B-MP, single row, solid brass cage



Informacje techniczne



Twoja aktualna wersja produktu

Design variant	B	B
Sealing	Without	Not sealed
Cage	MP	Solid brass cage, ball guided
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S1	Rings dimensional stabilized up to 200°
Bearing with matched conditions for fitting in pairs	UA	Bearing set with small axial internal clearance
Lubricant	Without	Bearing not greased

Main Dimensions & Performance Data

d	260 mm	Bore diameter
D	540 mm	Outside diameter
B	102 mm	Width
C _r	670.000 N	Basic dynamic load rating, radial
C _{0r}	1.180.000 N	Basic static load rating, radial
C _{ur}	30.500 N	Fatigue load limit, radial
n _G	1.800 1/min	Limiting speed
n _{gr}	1.140 1/min	Reference speed
≈m	113 kg	Masa



Mounting dimensions

$d_{a \min}$	286 mm	Minimum diameter of shaft shoulder
$D_{a \max}$	514 mm	Maximum diameter of housing shoulder
$D_{b \max}$	526 mm	Maximum diameter of housing shoulder
$r_{a \max}$	5 mm	Maximum fillet radius of shaft
$r_{a1 \max}$	2,5 mm	Maximum fillet radius of housing

Dimensions

$r_{\min}$	6 mm	Minimum chamfer dimension
$r_1 \min$	3 mm	Minimum chamfer dimension
D_1	432,95 mm	Shoulder diameter on outer ring wide side face
d_1	373,65 mm	Shoulder diameter on inner ring wide side face
a	218,8 mm	Distance between the apexes of the pressure cones
α	40 °	Contact angle

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	200 °C	Operating temperature max.

Additional information

Tol (+)	16 μ m	Tolerance for axial clearance or preload per set
$A_{\min}$	120 mm	Axial clearance per set min.



Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia



Łożysko gabarytowe