





812/600-M

Axial cylindrical roller bearing

Axial cylindrical roller bearing 812...-M, single row

Informacje techniczne



Twoja aktualna wersja produktu

Cage	M	Brass Cage
------	---	------------

Main Dimensions & Performance Data

d	600 mm	Bore diameter
T	160 mm	Height
C _a	5.500.000 N	Basic dynamic load rating, axial
C _{0a}	24.300.000 N	Basic static load rating, axial
C _{ua}	1.600.000 N	Fatigue load limit, axial
n _G	400 1/min	Limiting speed
n _{gr}	109 1/min	Reference speed
D	800 mm	Outside diameter
m	254,5 kg	Masa

Mounting dimensions

r _{a max}	5 mm	Maximum recess radius
--------------------	------	-----------------------

Dimensions

D ₁	605 mm	Bore diameter housing washer
d ₁	795 mm	Rip diameter shaft washer
r _{min}	5 mm	Minimum chamfer dimension



Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

Additional information

K812/600-M	Axial roller and cage assembly
GS812/600	Housing Washer
WS812/600	Shaft washer

Właściwości

-  Obciążenie osiowe jednokierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia