





81230-M

Axial cylindrical roller bearing

Axial cylindrical roller bearing 812...-M, single row

Informacje techniczne



Twoja aktualna wersja produktu

Cage	M	Brass Cage
------	---	------------

Main Dimensions & Performance Data

d	150 mm	Bore diameter
T	50 mm	Height
C _a	590.000 N	Basic dynamic load rating, axial
C _{0a}	1.940.000 N	Basic static load rating, axial
C _{ua}	191.000 N	Fatigue load limit, axial
n _G	1.580 1/min	Limiting speed
n _{gr}	610 1/min	Reference speed
D	215 mm	Outside diameter
m	6,5 kg	Masa

Mounting dimensions

d _{a min}	211 mm	Minimum diameter shaft shoulder
D _{a max}	158 mm	Maximum diameter of housing shoulder
r _{a max}	1,5 mm	Maximum recess radius



Dimensions

D ₁	153 mm	Bore diameter housing washer
d ₁	212 mm	Rip diameter shaft washer
r _{min}	1,5 mm	Minimum chamfer dimension

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Additional information

K81230-M	Axial roller and cage assembly
GS81230	Housing Washer
WS81230	Shaft washer

Właściwości

- 

Obciążenie osiowe jednokierunkowe
- 

Smarowanie smarem
- 

Smarowanie olejem
- 

Bez uszczelnienia