



81236-M

Axial cylindrical roller bearing

Axial cylindrical roller bearing 812...-M, single row

Informacje techniczne



Twoja aktualna wersja produktu

Cage	M	Brass Cage
------	---	------------

Main Dimensions & Performance Data

d	180 mm	Bore diameter
T	56 mm	Height
C _a	700.000 N	Basic dynamic load rating, axial
C _{0a}	2.440.000 N	Basic static load rating, axial
C _{ua}	232.000 N	Fatigue load limit, axial
n _G	1.340 1/min	Limiting speed
n _{gr}	520 1/min	Reference speed
D	250 mm	Outside diameter
m	9,088 kg	Masa

Mounting dimensions

d _{a min}	245 mm	Minimum diameter shaft shoulder
D _{a max}	190 mm	Maximum diameter of housing shoulder
r _{a max}	1,5 mm	Maximum recess radius



Dimensions

D ₁	183 mm	Bore diameter housing washer
d ₁	247 mm	Rip diameter shaft washer
r _{min}	1,5 mm	Minimum chamfer dimension

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Additional information

K81236-M	Axial roller and cage assembly
GS81236	Housing Washer
WS81236	Shaft washer

Właściwości

	Obciążenie osiowe jednokierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia