





81292-M

Axial cylindrical roller bearing

Axial cylindrical roller bearing 812...-M, single row

Informacje techniczne



Twoja aktualna wersja produktu

Cage	M	Brass Cage
------	---	------------

Main Dimensions & Performance Data

d	460 mm	Bore diameter
T	130 mm	Height
C _a	3.700.000 N	Basic dynamic load rating, axial
C _{0a}	15.500.000 N	Basic static load rating, axial
C _{ua}	1.110.000 N	Fatigue load limit, axial
n _G	520 1/min	Limiting speed
n _{gr}	147 1/min	Reference speed
D	620 mm	Outside diameter
m	121,78 kg	Masa

Mounting dimensions

d _{a min}	611 mm	Minimum diameter shaft shoulder
D _{a max}	499 mm	Maximum diameter of housing shoulder
r _{a max}	5 mm	Maximum recess radius



Dimensions

D ₁	465 mm	Bore diameter housing washer
d ₁	615 mm	Rip diameter shaft washer
r _{min}	5 mm	Minimum chamfer dimension

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Additional information

K81292-M	Axial roller and cage assembly
GS81292	Housing Washer
WS81292	Shaft washer

Właściwości

	Obciążenie osiowe jednokierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia