



89314-TV

Axial cylindrical roller bearing

Axial cylindrical roller bearings 893, single direction, comprising K893, GS, WS

Informacje techniczne



Twoja aktualna wersja produktu

Cage	TV	Plastic Cage made from PA66
------	----	-----------------------------

Main Dimensions & Performance Data

d	70 mm	Bore diameter
D	125 mm	Outside diameter
T	34 mm	Height
C _a	239.000 N	Basic dynamic load rating, axial
C _{0a}	830.000 N	Basic static load rating, axial
C _{ua}	76.000 N	Fatigue load limit, axial
n _G	2.950 1/min	Limiting speed
n _{gr}	1.200 1/min	Reference speed
m	1,796 kg	Masa

Mounting dimensions

d _a	123 mm	Minimum diameter shaft shoulder
D _a	76 mm	Maximum diameter of housing shoulder
r _a	1,1 mm	Recess radius



Dimensions

D ₁	72 mm	Bore diameter housing washer
d ₁	125 mm	Rip diameter shaft washer
B	34 mm	Width
r _{min}	1,1 mm	Minimum chamfer dimension
D _{c1}	70 mm	Cage bore diameter

Temperature range

T _{min}	-20 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Additional information

K89314-TV	Axial roller and cage assembly
GS89314	Housing Washer
WS89314	Shaft washer

Właściwości

	Obciążenie osiowe jednokierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia