



FAG

AK544090-544116

Tapered roller bearing

Tapered roller bearings K-Series, in inch sizes, separable

Informacje techniczne



Twoja aktualna wersja produktu

Tolerance class	ABMA4	Class 4 (ANSI/ABMA 19.2:2013)
Heat treatment	Standard	
Cage	Standard	Sheet steel cage, window cage, roller-guided
Quality level	Standard	
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	228,6 mm	Bore diameter
D	295,275 mm	Outside diameter
B	31,75 mm	Width, inner ring
C	23,813 mm	Width, outer ring
T	33,338 mm	Width, total
C _r	250.000 N	Basic dynamic load rating, radial
C _{0r}	510.000 N	Basic static load rating, radial
C _{ur}	57.000 N	Fatigue load limit, radial
n _G	2.320 1/min	Limiting speed
n _{gr}	1.320 1/min	Thermal speed rating
≈m	5,3 kg	Masa



Mounting dimensions

d _a max	246 mm	Maximum diameter of shaft shoulder
d _b min	250 mm	Minimum diameter of shaft shoulder
D _a min	278 mm	Minimum diameter of housing shoulder
D _a max	281 mm	Maximum diameter of housing shoulder
D _b min	284 mm	Minimum diameter of housing shoulder
C _a min	5 mm	Minimum axial space
C _b min	9,5 mm	Minimum axial space
r _a max	3,6 mm	Maximum fillet radius of shaft
r _b max	3,3 mm	Maximum fillet radius of housing

Dimensions

r _{1, 2} min	3,6 mm	Minimum chamfer dimension of inner ring back face
r _{3, 4} min	3,3 mm	Minimum chamfer dimension of outer ring back face
a	50 mm	Distance between the apexes of the pressure cones
d ₁	262,5 mm	Guidance rib diameter of inner ring

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	200 °C	Operating temperature max.

Calculation factors

e	0,4	Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y
Y	1,49	Dynamic axial load factor
Y ₀	0,82	Static axial load factor



Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia