




ARCALUB-C2-2P

Automatic lubricator CONCEPT

CONCEPT2, Multi-point lubricator

Informacje techniczne



Twoja aktualna wersja produktu

Drive System	PP	Piston pump
Lubricant volume	V250/300	250/300 cm³

Technical data

	Piston pump	Functional principle
V Lub	250 cm³	Lubricant volume
	0,15 cm³	Metering quantity (per outlet and stroke/impulse)
P op	30 bar	Operating pressure, max.
	≤ NLGI 2 (suitability test required)	Lubricant
n pb	2	Number of pump bodies
n out	2	Number of outlets
	≤ 2	Number of lubrication points: direct
	≤ 4	Number of lubrication points: with splitters
	> 4	Number of lubrication points: with progressive distributors
	PA hose	Connection
U op	3-V lithium-metal battery	Operating voltage
	microelectronic	Controller (integrated)
	PLC	Controller (extern)
	Integrated, electronic	Monitoring: pressure
	External (PLC)	Monitoring: fill level
	Empty level, back pressure, internal error (PLC)	Error message
	IP54	Protection class
	Polyamide	Housing material
t min	-20 °C	Operating temperature, min.
t max	70 °C	Operating temperature, max.
	vertical	Mounting position
	91 x 223 x 112	Dimensions (mm)

1 kg Masa