

AXK1024-A/0-10

Axial needle roller and cage assembly

Axial needle roller and cage assemblies,
single direction, to DIN 5405-2

Informacje techniczne





Main Dimensions & Performance Data

D_{c1}	10 mm	Bore diameter cage
D_c	24 mm	Outside diameter
D_w	2 mm	Rolling element diameter
E_a	23 mm	Raceway dimension
E_b	12 mm	Raceway dimension
c_a	9.200 N	Basic dynamic load rating, axial
c_{0a}	25.500 N	Basic static load rating, axial
c_{ua}	2.550 N	Fatigue load limit, axial
n_G	16.900 1/min	Limiting speed
$n_{\vartheta r}$	7.400 1/min	Reference speed
≈m	3,107 g	Masa

Temperature range

T_{min}	-20 °C	Operating temperature min.
T_{max}	120 °C	Operating temperature max.

Additional information

	AS1024	Axial bearing washer

Karta katalogowa jest jedynie przeglądem wymiarów i podstawowych nośności wybranego produktu. Zawsze należy stosować się do wszystkich dalszych informacji i instrukcji dotyczących tego produktu. Na naszej stronie internetowej znajduje się formularz kontaktowy umożliwiający wysłanie zapytania o dalsze informacje