


FAG

B71919-E-T-P4S-UL

Spindle bearing

Spindle bearing B719...-E, adjusted, in pairs or sets, contact angle $\alpha = 25^\circ$, restricted tolerances

Informacje techniczne





Twoja aktualna wersja produktu

Preload class	L	Preload light
Contact angle	E	Contact angle 25°
Tolerance class	P4S	Tolerance class P4S, FAG standard better than P4 to ISO 492:2023
Type of Seal	Without	Not sealed
Cage	T	Laminated fabric cage
Arrangement bearing set	U	Single bearing

Main Dimensions & Performance Data

d	95 mm	Bore diameter
D	130 mm	Outside diameter
B	18 mm	Width
C _r	46.000 N	Basic dynamic load rating, radial
C _{0r}	34.500 N	Basic static load rating, radial
C _{ur}	3.450 N	Fatigue load limit, radial
n _{G Grease}	9.000 1/min	Limiting speed for grease lubrication
n _{G Oil}	14.000 1/min	Limiting speed for oil lubrication
≈m	0,571 kg	Masa





Mounting dimensions

d _a	102 mm	Diameter shaft shoulder
d _a	h12	Diameter shaft shoulder clearance
D _a	124 mm	Shoulder diameter outer ring
D _a	H12	
r _a max	0,6 mm	Maximum recess radius
r _{a1} max	0,6 mm	Maximum recess radius
E _{tk} min	105,9 mm	Minimum diameter injection pitch
E _{tk} max	109,2 mm	Maximum diameter injection pitch
E _{tk1} min	105,9 mm	Minimum diameter injection pitch
E _{tk1} max	109,2 mm	Maximum diameter injection pitch
a	35,2 mm	Distance between the apexes of the pressure cones

Dimensions

r _{min}	1,1 mm	Minimum chamfer dimension
r ₁ min	1,1 mm	Minimum chamfer dimension
α	25 °	Contact angle

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	100 °C	Operating temperature max.



Additional information

F_{VL}	341 N	Preload force light
F_{VM}	1.262 N	Preload force medium
F_{VH}	2.693 N	Preload force heavy
K_{aEL}	988 N	Lift-off force light
K_{aEM}	3.777 N	Lift-off force medium
K_{aEH}	8.313 N	Lift-off force heavy
c_{aL}	196 N/ μ m	Axial rigidity light
c_{aM}	319 N/ μ m	Axial rigidity medium
c_{aH}	434 N/ μ m	Axial rigidity heavy

Właściwości

- 

Obciążenie promieniowe
- 

Obciążenie osiowe jednokierunkowe
- 

Smarowanie smarem
- 

Smarowanie olejem
- 

Bez uszczelnienia