






FAG

B7212-E-2RSD-T-P4S-UL

Spindle bearing

Spindle bearing B72...-E-2RSD, adjusted, in pairs or sets, contact angle $\alpha = 25^\circ$, lip seals on both sides, non-contact, restricted tolerances

Informacje techniczne



Twoja aktualna wersja produktu

Preload class	L	Preload light
Contact angle	E	Contact angle 25°
Tolerance class	P4S	Tolerance class P4S, FAG standard better than P4 to ISO 492:2023
Cage	T	Laminated fabric cage
Arrangement bearing set	U	Single bearing
Lubricant	GA21	Grease for super precision bearings, standard

Main Dimensions & Performance Data

d	60 mm	Bore diameter
D	110 mm	Outside diameter
B	22 mm	Width
C _r	53.000 N	Basic dynamic load rating, radial
C _{0r}	29.500 N	Basic static load rating, radial
C _{ur}	3.150 N	Fatigue load limit, radial
n _{G Grease}	12.000 1/min	Limiting speed for grease lubrication
≈m	0,79 kg	Masa



Mounting dimensions

d _a	69,5 mm	Diameter shaft shoulder
d _a	h12	Diameter shaft shoulder clearance
D _a	101,5 mm	Shoulder diameter outer ring
D _a	H12	
r _{a max}	1,5 mm	Maximum recess radius
r _{a1 max}	0,6 mm	Maximum recess radius
a	30,9 mm	Distance between the apexes of the pressure cones

Dimensions

r _{min}	1,5 mm	Minimum chamfer dimension
r _{1 min}	1,5 mm	Minimum chamfer dimension
α	25 °	Contact angle

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	80 °C	Operating temperature max.

Additional information

F _{V L}	463 N	Preload force light
F _{V M}	1.586 N	Preload force medium
F _{V H}	3.304 N	Preload force heavy
K _{aE L}	1.351 N	Lift-off force light
K _{aE M}	4.794 N	Lift-off force medium
K _{aE H}	10.334 N	Lift-off force heavy
c _{a L}	165 N/μm	Axial rigidity light
c _{a M}	264 N/μm	Axial rigidity medium
c _{a H}	358 N/μm	Axial rigidity heavy



Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Smarowanie dożywotnie, bezobsługowe



Smarowanie smarem



Uszczelnienie dwustronne