


BK0609

Drawn cup needle roller bearing closed end

Drawn cup needle roller bearings with closed end BK, to DIN 618/ISO 3245

Informacje techniczne



Twoja aktualna wersja produktu

Lubricant	Without
Lubrication hole	Without
Coating	Without
Sealing	Without

Main Dimensions & Performance Data

F _w	6 mm	Under roller diameter
D	10 mm	Outside diameter
C	9 mm	Width, outer ring
C _r	2.850 N	Basic dynamic load rating, radial
C _{0r}	2.600 N	Basic static load rating, radial
C _{ur}	320 N	Fatigue load limit, radial
n _G Grease	21.900 1/min	Limiting speed for grease lubrication
n _G	36.500 1/min	Limiting speed
n _{gr}	30.500 1/min	Reference speed
≈m	2,6 g	Masa

Dimensions

r _{min}	0,4 mm	Minimum chamfer dimension
C _{t min}	7,4 mm	Minimum width to base of drawn cup with closed end



Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
------------	--------	----------------------------

$T_{\max}$	140 °C	Operating temperature max.
------------	--------	----------------------------

Additional information

GR6X10X2

Sealing ring

Właściwości



Obciążenie promieniowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia



Mała przestrzeń zabudowy