


BK1012 [↗](#)
Drawn cup needle roller bearing closed end
Drawn cup needle roller bearings with closed end BK, to DIN 618/ISO 3245

Informacje techniczne



Twoja aktualna wersja produktu

Lubricant	Without
Lubrication hole	Without
Coating	Without
Sealing	Without

Main Dimensions & Performance Data

F _w	10 mm	Under roller diameter
D	14 mm	Outside diameter
C	12 mm	Width, outer ring
C _r	5.500 N	Basic dynamic load rating, radial
C _{0r}	6.800 N	Basic static load rating, radial
C _{ur}	950 N	Fatigue load limit, radial
n _G Grease	14.600 1/min	Limiting speed for grease lubrication
n _G	24.300 1/min	Limiting speed
n _{gr}	18.400 1/min	Reference speed
≈m	4,968 g	Masa

Dimensions

r _{min}	0,4 mm	Minimum chamfer dimension
C _{t min}	10,4 mm	Minimum width to base of drawn cup with closed end



Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	140 °C	Operating temperature max.

Additional information

GR10X14X3	Sealing ring
G10X14X3	Sealing ring 2
IR7X10X12-XL	Suitable inner rings IR

Właściwości

	Obciążenie promieniowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia
	Mala przestrzeń zabudowy