


BK2018-RS

Drawn cup needle roller bearing closed end

Drawn cup needle roller bearings with closed end BK...-RS, lip seal on one side

Informacje techniczne



Twoja aktualna wersja produktu

Lubricant	L271	Grease (L271/customer specific)
Lubrication hole	Without	
Coating	Without	
Type of Seal	RS	Contact seal on one sides

Main Dimensions & Performance Data

F _w	20 mm	Under roller diameter
D	26 mm	Outside diameter
C	18 mm	Width, outer ring
C _r	12.700 N	Basic dynamic load rating, radial
C _{0r}	20.100 N	Basic static load rating, radial
C _{ur}	2.550 N	Fatigue load limit, radial
n _G Grease	7.600 1/min	Limiting speed for grease lubrication
n _G	7.600 1/min	Limiting speed
m	24 g	Masa

Dimensions

r _{min}	0,8 mm	Minimum chamfer dimension
C _{t min}	15,3 mm	Minimum width to base of drawn cup with closed end



Temperature range

T_{min}	-20 °C	Operating temperature min.
T_{max}	100 °C	Operating temperature max.

Właściwości



Obciążenie promieniowe



Smarowanie smarem



Uszczelnienie jednostronne



Mała przestrzeń zabudowy