

**BKE.TSX35-D**

## Braking/clamping element

Braking and clamping element BKE.TSX...-D, hydraulic connector on end face, for linear recirculating roller bearing and guideway assembly

## Informacje techniczne

## Twoja aktualna wersja produktu

|         |    |
|---------|----|
| Size    | 35 |
| Version | D  |

## Main Dimensions &amp; Performance Data

|    |         |                                       |
|----|---------|---------------------------------------|
| H  | 48 mm   | Height sytem                          |
|    | without | Adapter plate                         |
| B  | 69 mm   | Width of braking and clamping element |
| L  | 120 mm  | Length braking and clamping element   |
|    | 2.800 N | Clamping force                        |
| ≈m | 1,58 kg | Masa                                  |

## Dimensions

|                 |         |                                         |
|-----------------|---------|-----------------------------------------|
| J <sub>B</sub>  | 58 mm   | Hole pattern                            |
| J <sub>C</sub>  | 48 mm   | Hole pattern                            |
| A <sub>1</sub>  | 13,5 mm | Distance                                |
| J <sub>L</sub>  | 100 mm  | Hole pattern                            |
| H <sub>1</sub>  | 6,6 mm  | Space (system)                          |
| H <sub>3</sub>  | 8,1 mm  | Mounting dimension                      |
| A <sub>L2</sub> | 5 mm    | Distance                                |
| d <sub>1</sub>  | M8x1    | Size thread                             |
| G <sub>2</sub>  | M8      | Size thread above for DIN ISO 4762-12.9 |
| M <sub>A</sub>  | 42,2 Nm | Tightening torque above                 |

