


CRB20/83-XL

Radial insert ball bearing

Radial insert ball bearings CRB, with rubber interliner, location by eccentric locking collar, P seals on both sides

X-life

Informacje techniczne



Main Dimensions & Performance Data

d	20 mm	Bore diameter
D	83,6 mm	Outside diameter
C	25,4 mm	Width, outer ring
B 2	36,2 mm	Width total
B 1	31 mm	Locking collar total width
C r	12.800 N	Basic dynamic load rating, radial
C 0r	6.600 N	Basic static load rating, radial
C ur	315 N	Fatigue load limit, radial
	750 N	Load carrying capacity (rubber interliner)
≈m	0,3 kg	Masa

Dimensions

D 1	87,4 mm	Flange diameter
C 1	4,8 mm	Thickness of flange
D 2	40 mm	Flange diameter rubber interliner
d 3	33 mm	Outside diameter locking collar/locknut
S 2	12,7 mm	Distance raceway to rubber interliner flange side

Calculation factors

f 0	13,1	Calculation factor
-----	------	--------------------



Additional information

RAE20-XL-NPP		Bearing designation
Shore A	80 °	Hardness rubber interliner

Właściwości

- 

Obciążenie promieniowe
- 

Obciążenie osiowe jednokierunkowe
- 

Obciążenie osiowe dwukierunkowe
- 

L_h Smarowanie dożywotnie, bezobsługowe
- 

Smarowanie smarem
- 

Uszczelnienie dwustronne