




EP-13S-120V

Hydraulic pump, electric

BETEX EP-13, 700 bar, usable oil volume 2.4 l

Informacje techniczne



Twoja aktualna wersja produktu

Series	EP	Electric pump
Version	HC	For use with hydraulic cylinders

Technical data

P max	700 bar	Maximum operating pressure
$\dot{V}_{H0}$	4.000 cm ³	Flow rate/minute, without load
$\dot{V}_{H350}$	330 cm ³	Flow rate/minute @ 350 bar
$\dot{V}_{H700}$	280 cm ³	Flow rate/minute @ 700 bar
V max	3 l	Volume of oil container
V eff	2,4 l	Useable oil quantity
	single-acting	Cylinder compatibility
	2 pos./2-way	Valve type
	Hold/reverse	Valve function
U	120 V	Operating voltage
f	50 – 60 Hz	Power frequency
I	10 A	Amperage
	single-phase	Motor type
P M	0,45 kW	Motor power
	≈ 80 dB	Noise level @ 700 bar
≈m	25,8 kg	Masa



Dimensions

A	511,5 mm
B	148,5 mm
C	295,5 mm
D	251 mm
E	406 mm
F	206,5 mm
G	149,4 mm
H	3/8" NPT
J	485 mm

Additional information

Motor thermally
protected, remote
control with
3 m cable, automatic
overload valve
(700 bar)

Product specifics