



**FLCTEY20-XL**

Flanged housing unit

Housing units FLCTEY, two-bolt flanged housing units, cast iron, grub screws in inner ring, P seals, without relubrication facility

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Material	GG	Grey cast iron
----------	----	----------------

Main Dimensions & Performance Data

d	20 mm	Bore diameter
L	66,5 mm	Flange width
H	90,5 mm	Height flange
U	27 mm	Total height unit
C _r	13.600 N	Basic dynamic load rating, radial
C _{0r}	6.600 N	Basic static load rating, radial
C _{ur}	345 N	Fatigue load limit, radial
≈m	0,31 kg	Masa

Mounting dimensions

J	71,4 mm	Distance fixing bore
J	71,4 mm	Pitch circle diameter (holes)
N	9 mm	Fixing bore
n	2	Number of screwing holes



Dimensions

A ₁	17 mm	Thickness of flange
A ₂	9,5 mm	Distance raceway
d ₃	33 mm	Outside diameter eccentric locking collar

Additional information

1	Number of housings
LCTE04	Housing
AY20-XL-NPP-B	Bearing designation

Temperature range

T _{min}	-20 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.