


**GAKL14-PW**

Rod end

Rod end GAKL...-PW, external threads,
maintenance-free

Informacje techniczne



Twoja aktualna wersja produktu

Clampable	Not clampable
Grease nipples	Cannot be relubricated
Slotted	No
Thread Pitch	Left-hand thread
Maintenance	Maintenance free
Type of Seal	Without
Material sliding Layer	Sliding foil
Mounting bolt	External thread

Main Dimensions & Performance Data

d 2	36 mm	Outer diameter eye
C r	31.000 N	Basic dynamic load rating
C 0r	32.000 N	Basic static load rating
d	14 mm	Bore diameter bearing
D	28 mm	Outside diameter bearing
l 2	78 mm	Total length
B	19 mm	Width inner ring
≈m	0,16 kg	Masa



Dimensions

d _k	25,4 mm	Ball diameter
d ₁	16,8 mm	Outer flange diameter inner ring
d ₃	M14	Thread size
h	60 mm	Length of thread
C ₁	13,5 mm	Width of the rod end
alpha	16 °	Tilt angle
l ₁	36 mm	Thread length
l ₇	18 mm	Length of the flat surface from the bearing bore centre to the shank
B _{UT}	-0,12 mm	Width inner ring , lower tolerance
B _{OT}	0 mm	Width inner ring; upper tolerance
d _T	H7	Bore diameter_bearing_tolerance
d _{UT}	0 mm	Bore diameter, lower tolerance
d _{OT}	0,018 mm	Bore diameter bearing upper tolerance
G _r	0 - 0,035	Radial clearance
G _{rmax}	0,035 mm	Radial clearance, maximum
G _{rmin}	0 mm	Radial clearance, minimum

Temperature range

T _{min}	-50 °C	Operating temperature min.
T _{max}	200 °C	Operating temperature max.

Mounting dimensions

r _{1s}	0,3 mm	Smallest single chamfer dimension, inner ring
-----------------	--------	---



Właściwości



Obciążenie promieniowe



Smarowanie dożywotnie, bezobsługowe



Bez uszczelnienia



Nieosiowość statyczna



Nieosiowość dynamiczna