




GAY25-XL-NPP-B

Radial insert ball bearing

Radial insert ball bearings GAY...NPP-B,
spherical outer ring, location by grub screws,
P seals on both sides

X-life

Informacje techniczne



Main Dimensions & Performance Data

d	25 mm	Bore diameter
D SP	52 mm	Outside diameter
B	27 mm	Width
C 0r	7.800 N	Basic static load rating, radial
C ur	410 N	Fatigue load limit, radial
C r	14.000 N	Basic dynamic load rating, radial
≈m	0,15 kg	Masa

Dimensions

C	15 mm	Width, outer ring
S	7,5 mm	Distance raceway
d 1	33,5 mm	Rib diameter inner ring
d 2	30,4 mm	Rib diameter sealing inner ring
C a	3,9 mm	Distance to lubrication hole
A	5 mm	Distance thread
W	2,5 mm	Width of flats

Temperature range

T min	-20 °C	Operating temperature min.
T max	120 °C	Operating temperature max.



Calculation factors

f_0	13,8	Calculation factor
-------	------	--------------------

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie dożywotnie, bezobsługowe
	Smarowanie smarem
	Uszczelnienie dwustronne
	Nieosiowość statyczna