


GE17-AX

Spherical plain bearing

Axial spherical plain bearing, requiring maintenance, sliding contact surface: steel/ steel

Informacje techniczne



Twoja aktualna wersja produktu

Maintenance	Maintenance required	
Coating	Durotect M	Inner- and outer ring coated with Durotect M (Manganese Phosphate)

Main Dimensions & Performance Data

d	17 mm	Inner diameter bearing
D	47 mm	Outside diameter bearing
T	16 mm	Height
C _a	77.000 N	Basic dynamic load rating, axial
C _{0a}	296.000 N	Basic static load rating, axial
≈m	0,159 kg	Masa

Mounting dimensions

r ₁ min	0,6 mm	Edge Spacing
r ₂ min	0,2 mm	Edge Spacing
d _a max	34 mm	Connection measure Inner ring
D _a min	30,5 mm	Housing Connection Diameter



Dimensions

d _K	50 mm	Ball diameter
d ₃	34	Front surface diameter of shaft washer
D ₁	28 mm	Inner diameter of housing washer
B	11,5 mm	Width Inner ring
C	11,5 mm	Width Outer ring
s	11 mm	Plane Surface Spacing
A	5 mm	Distance lubrication Bore
α	6 °	Tilt angle
d _{OT}	0 mm	Bore diameter bearing, upper tolerance
d _{UT}	-0,008 mm	Bore diameter bearing, lower tolerance
D _{OT}	0 mm	Outer diameter, upper tolerance
D _{UT}	-0,011 mm	Outside diameter, lower tolerance
T _{OT}	0 mm	Height, upper tolerance
T _{UT}	-0,4 mm	Height, lower tolerance
C _{UT}	0 mm	Width outer ring, upper tolerance
C _{OT}	-0,24 mm	Width outer ring, lower tolerance
B _{OT}	0 mm	Width inner ring, upper tolerance
B _{UT}	-0,24 mm	Width inner ring, lower tolerance
d ₂	43,4 mm	Connection measure Inner ring

Temperature range

T _{min}	-60 °C	Operating temperature min.
T _{max}	200 °C	Operating temperature max.



Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Smarowanie smarem



Bez uszczelnienia



Nieosiowość statyczna



Nieosiowość dynamiczna