




GE25-KRR-B-FA107-VA-FD [🔗](#)

Radial insert ball bearing

Informacje techniczne



Main Dimensions & Performance Data

d	25 mm	Bore diameter
D _{SP}	52 mm	Outside diameter
B	21,5 mm	Width
C _{0r}	7.880 N	Basic static load rating, radial
C _{ur}	335 N	Fatigue load limit, radial
B ₁	31 mm	Locking collar total width
C _r	14.020 N	Basic dynamic load rating, radial
≈m	0,2 kg	Masa

Dimensions

C	15 mm	Width, outer ring
S	7,5 mm	Distance raceway
d ₁	34 mm	Rib diameter inner ring
C _a	4,15 mm	Distance to lubrication hole
d ₃	38,1 mm	Outside diameter locking collar/locknut
W	3 mm	Width of flats

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	100 °C	Operating temperature max.



Calculation factors

f_0	13,8	Calculation factor
-------	------	--------------------

Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie dożywotnie, bezobsługowe
-  Smarowanie smarem
-  Uszczelnienie dwustronne
-  Ochrona przed korozją
-  Nieosiowość statyczna