




GE40-XL-KRR-B-2C

Radial insert ball bearing

Radial insert ball bearings GE...KRR-B-2C,
spherical outer ring, location by eccentric
locking collar, R seals on both sides

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Flinger shields	2C	Flinger shield on both sides
-----------------	----	------------------------------

Main Dimensions & Performance Data

d	40 mm	Bore diameter
D SP	80 mm	Outside diameter
B	42,9 mm	Width
C 0r	19.800 N	Basic static load rating, radial
C ur	940 N	Fatigue load limit, radial
B 1	56,5 mm	Locking collar total width
C r	34.500 N	Basic dynamic load rating, radial
≈m	0,78 kg	Masa

Dimensions

C	21 mm	Width, outer ring
C 2	31,9 mm	Sealing total width
S	21,4 mm	Distance raceway
d 1	52,3 mm	Rib diameter inner ring
C a	6,4 mm	Distance to lubrication hole
d 3	58 mm	Outside diameter locking collar/locknut
W	5 mm	Width of flats



Calculation factors

f ₀	13,6	Calculation factor
----------------	------	--------------------

Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie dożywotnie, bezobsługowe
-  Smarowanie smarem
-  Uszczelnienie dwustronne
-  Nieosiowość statyczna