


**GE60-XL-KTT-B**

Radial insert ball bearing

Radial insert ball bearings GE...KTT-B,
spherical outer ring, location by eccentric
locking collar, T seals on both sides

X-life

Informacje techniczne

**Main Dimensions & Performance Data**

d	60 mm	Bore diameter
D _{SP}	110 mm	Outside diameter
B	61,9 mm	Width
C _{0r}	36.000 N	Basic static load rating, radial
C _{ur}	1.710 N	Fatigue load limit, radial
B ₁	77,9 mm	Locking collar total width
C _r	52.000 N	Basic dynamic load rating, radial
≈m	1,789 kg	Masa

Dimensions

C	24 mm	Width, outer ring
C ₂	29 mm	Sealing total width
S	31 mm	Distance raceway
d ₁	76,5 mm	Rib diameter inner ring
D ₁	94,5 mm	Outside diameter seal
C _a	7,2 mm	Distance to lubrication hole
d ₃	84 mm	Outside diameter locking collar/locknut
W	5 mm	Width of flats



Calculation factors

f_0	14,3	Calculation factor
-------	------	--------------------

Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie dożywotnie, bezobsługowe
-  Smarowanie smarem
-  Uszczelnienie dwustronne
-  Nieosiowość statyczna