




GIHNRK32-LO

Rod end

Hydraulic rod end, with thread clamping device, right hand thread, requiring maintenance, sliding contact surface: steel/ steel, DIN 24338 ISO 6982, open design

Informacje techniczne



Twoja aktualna wersja produktu

Clampable	Clampable	
Maintenance	Maintenance required	
Lubrication nipple	DIN71412-AM6 (tapered grease nipple)	
Slotted	Slotted, both sides	
Thread Pitch	Right-hand thread	
Type of Seal	Without	
Radial internal clearance	CN (Group N)	Normal internal clearance
Mounting	Internal thread clampable	

Main Dimensions & Performance Data

C _r	87.500 N	Basic dynamic load rating, radial
C _{0r}	126.000 N	Basic static load rating, radial
d	32 mm	Bore diameter bearing
d ₂	70 mm	Outer eye diameter
l ₄	118,5 mm	Total length internal thread head
D	52 mm	Outside diameter bearing
B	32 mm	Width inner ring
≈m	1,16 kg	Masa



Dimensions

α	4 °	Tilt angle
C 1	28 mm	Width of the rod end
C 2	22 mm	Width
d K	44 mm	Ball diameter
d 3	M27x2	Thread size
d 4	34 mm	Shank diameter
d 5	66 mm	Shank diameter, large
d 7	M10x25	Diameter screw clamp
h 1	80 mm	Shank Length Internal thread head
l 3	37 mm	Thread length Internal thread
l 7	32 mm	Distance drilling with/shaft start
d UT	0 mm	Bore diameter bearing, lower tolerance
d T	H7	Bore diameter bearing, tolerance
d OT	0,025 mm	Bore diameter bearing, upper tolerance
B UT	-0,32 mm	Width inner ring, lower tolerance
B OT	0 mm	Width inner ring, upper tolerance
M A	64 Nm	Tightening torque
F Z	50.000 N	Cylinder Force
G r	CN	Radial Clearance
G rmin	0,025 mm	Radial clearance, minimum
G rmax	0,1 mm	Radial clearance, maximum

Mounting dimensions

r 1smin	0,6 mm	Edge Spacing
d 1	38 mm	Outer flange diameter inner ring



Temperature range

T_{min}	-60 °C	Operating temperature min.
T_{max}	200 °C	Operating temperature max.

Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Obciążenie osiowe dwukierunkowe



Smarowanie smarem



Bez uszczelnienia



Nieosiowość statyczna



Nieosiowość dynamiczna